

BLUE 5500 for AdBlue®

optimum size & capacity



Capacity: 5500 l

Options:




fleet management



iTANK telemetry



dispensing accessories in service room



longer hose

Standard:



double wall tank



service door for maintenance



SS piping & construction



2" dry break coupling for cistern connection



sound & light overfill alarm



submersible pump with dry run sensor



openings for forklift



service room lightening



automatic nozzle



automatic nozzle holder



loose 6m hose



mechanical level indicator



LCR meter with impulse signal



fan/heating (depending on climate)

BASIC 5500 for AdBlue®

CAPACITY, DIMENSIONS & WEIGHT



TECHNICAL SPECIFICATION

Power Supply	1 x 230V / 50 Hz
Pump Efficiency	max. 40l/min
Pump Pressure	2,5 bar
Dry Break Coupling	DN d-50 mm
Overfill protection	24V
Cable connection	3 x 1,5 - 2,5mm ²
Operating Conditions	-20°C to +45°C

MATERIALS

Outer tank	polyethylene
Inner tank	polyethylene
Pipes	stainless steel
Hose	EPDM DN 19
Nozzle	stainless steel & PE cover



Storage Partners Group Sp. z o.o.
Gipsowa 11 street, 62-080 Sierosław (Poznań)
tel. +48 61 814 79 68
salesoffice@storage-partners.com
www.storage-partners.com