

# Data Sheet / Wayne Helix™ 6000 II CNG fuel dispenser

Lower Greenhouse Gas Emissions

## Fuel Compatibility

- Compressed Natural Gas (CNG)

## Model Availability

- Orientation: Lane, Dual-sided or Single-Sided
- Grades available: 1
- Nozzles available: 1 to 2. Also available as a back-2-back model for up to 5 grades in total
- Hydraulic System: Remote Pressure
- Pressure banks: External or 1 to 3
- Hose Management: Light Hose Retraction (LHR)
- Flow Rates available: up to 80 kg/min

## Hanging Hardware

- Nozzle Types: NGV1, NGV2
- Hose Sizes: 3/8", 1/2"

## Hose Reach

- LHR: 4.3 meter reach

## Electronics

- iGem pump computer

## Displays

- Premium 7-6-5 LED with 1.15" digits

## Totalizers

- Electromechanical 7-digit totalizers

## Communication Protocol

- DART as standard. Other protocols available

## Metering

- Mass flow meter

## Branding

- Optional customized graphics

## Materials

- Painted hot dipped galvanized steel frame
- Painted hot dipped galvanized steel cladding

## Corrosion Protection

- C4 protection according to ISO12944-2:1998 as standard

## Operating temperature

- From -25°C to +55°C as standard
- Optional low temperature kit option for extended temperature range -40°C to +60°C

## Relative Humidity

- From 5% to 95%

## IP Rating

- IP 54 electronic head

## Certifications

- ATEX
- OIML
- MID



DFS Worldwide Brands