# TULIP 1500 for AdBlue®



AdBlue® · Batteries · Green Solutions















for trucks & passenger cars



## capacities: 1.500 I

## **Opciones:**







loose hose



heated hose



telemetry

## Standard:



double skin tank (2 tanks)



movable roof for maintenance



stainless steel construction & piping



2" dry break coupling for cistern filling



openings for forklift



submersible pump with dry run protection



sound & light overfill alarm



mechanical level indicator

heating/ cooling system (depends on climate conditions)

## **TULIP 1500 - TYPES & DIMENSIONS**

# TULIP storage 155 cm ready to be connected to free standing dispenser with MID approval

#### TULIP petrol station ver. Comfort



with hanging hose up to 2,8 m

#### TULIP petrol station ver. Premium



with hose reel (up to 4,5 m) nozzle located side

## TULIP storage



ready to be connected to free standing dispenser

## **TULIP** comfort



with hanging hose up to 2,8 m

## **TULIP** premium



with hose reel (up to 4,5 m) nozzle located side

## **TECHNICAL SPECIFICATION**

Power Supply1 x 230V / 50 HzDry Break CouplingDN d-50 mmOverfill Protection230 V / 50 HzCable Connection $3 \times 1,5 - 2,5 \text{ mm}^2$ Operating Conditions $-20^{\circ}\text{C} - + 45^{\circ}\text{C}$ Hose Lenghtup to 2,8 m

#### **MATERIALS**

External tank fiberglass
Inner tank polyethylene
Pipes stainless steel
Hose EPDM DN 19

Nozzle stainless steel & PE cover

# TULIP 1500 is available in following nozzle versions:



for TRUCK flowrate: 4-40 l/min



for Passenger Cars (PC) flowrate: 2-10 l/min



for TRUCK & Passenger Cars (PC)





